




# EU Strategy to Fusion Power

Presented by Xavier Litaudon for EUROfusion



This work has been carried out within the framework of the EUROfusion Consortium and has received funding from the Euratom research and training programme 2014-2018 under grant agreement No 633053. The views and opinions expressed herein do not necessarily reflect those of the European Commission.

## EU Roadmap to the realisation of fusion energy (2012)



<http://www.euro-fusion.org/>

Area	Timeline / Key Milestones
1. Plasma operation	H2020: Inductive, Steady state; 2020-2030: JET, MSTs + International Collaborators; 2030-2050: Q=10
2. Heat exhaust	Baseline strategy; Advanced configuration and materials; JET, MSTs, PFC test facilities, DTF Facility + International Collaborators
3. Materials	Parallel Blanket Concepts; CFETR (CN), FNSF (US)
4. Tritium breeding	ITER Test Blanket programme; Parallel Blanket Concepts; CFETR (CN), FNSF (US)
5. Safety	DEMOS decision; Fusion electricity
6. DEMO	Construction; Fusion electricity
7. Low cost	Low capital cost and long term technologies
8. Stellarator	Stellarator optimization; Burning Plasma; Stellarator; W7-X + International Collaborators

- Joint EU programme with clear goal
- ITER: the key facility & critical path
- DEMO construction after ITER Q=10 and a single step to a commercial fusion power plant
- 2016 EU roadmap adaptation with revised ITER schedule

[F. Romanelli et al 2012]

Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 2

## Gaps to Fusion Energy

### 1) Sustainment of high gain burning plasma

- Control of Burning plasma, long duration, heat exhaust

### 2) Materials resistant to high heat fluxes and neutron fluence

appm He

displacement damage (dpa)

Tritium available (kg)

kg T / year

Date

### 3) Tritium cycle & T self-sufficiency

- ~112kg T/year for 500MWe reactor
- Efficient breeding & extraction
- **DEMO MUST operate and produce its own tritium around 2050**

Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 3

## Outline: Europe doing all possible to

Exploit recent advances in physics and technology to minimise the impact of the revised ITER timeline on the demonstration of fusion electricity:

- **Support ITER construction and Optimise ITER operation**
  - Risk mitigation for ITER by doing supporting research in contemporary devices
- **Ensure minimal delay to DEMO**
  - Conceptual design System Engineering Approach
  - Address universal technical challenges with gaps beyond ITER
    - safety, T-breeding, power exhaust, remote handling, component lifetime and plant availability

Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 4

## Research Issues\* during ITER Construction

### Key issues for the supporting Physics Research Programme accompanying ITER construction

- Plasma-Wall Interaction
- H-mode and access conditions to high confinement
- Scenario development
- MHD stability control

**Issues strongly linked: integrate results into 'flight simulator' for ITER experimental preparation & validation**

### Impact on ITER by


- affecting the design of 'permanent' components
- affecting 'upgradeable' components
- leading to improvements in scenarios & experimental plan towards Q=10

[\*ITER Council-Science and Technology Advisory Committee, 8<sup>th</sup> Meeting 2010 ITER\_D\_346RPL\_v1-1 IC-STAC-8/2.5]  
Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 5

## Prepare ITER operation: increase EU coordination

- **JET, Medium Size Tokamaks ASDEX Upgrade, TCV, MAST-U, WEST, linear PFC facilities and W7-X**
- **Address issues where EU coordination brings added value:**
  - Scaling to JT-60SA, ITER and reactors conditions
  - Operation with core & edge integration, High power steady-state
  - Divertor & PWI issues, ELMs mitigation, Disruptions
  - Diagnostics, Shaped configurations, Tight aspect ratios physics, ...
- **Integration of knowledge through theory and modelling**
- **Systematic extrapolation for JT-60SA, ITER and DEMO**
- **Prepare EU to JT-60SA operation**
- **Internationalization of JET to prepare ITER Q=10 operation**





### Proposal for ITER risk mitigation

- **Use contemporary fusion devices as ITER risk mitigation**
  1. lower the risk for further ITER delays
  2. reduce the time needed to achieve ITER  $Q_{DT}=10$
  3. identify potential obstacles early enough, allowing time for alternative strategies
- **Reduce the ITER non-active phase by proper preparation and training on JET and JT-60SA**
  - Make longer use of JET as risk mitigation for ITER and train the ITER generation of operators, session leaders, sci-techs, etc.
- **Impact on ITER by leading to improvements in operation, scenarios & experimental plan**
  - Prepare ITER non-active phase and  $Q_{DT}=10$  operation:
    - JET He, D, H, T, DT with ITER materials, T cycle, remote handling
    - JT-60SA with controlled long pulse baseline/hybrid operation
  - Prepare ITER  $Q_{DT}=5$  operation and DEMO scenarios on JT-60SA


Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 8

## Proposal: JET internationalized



- JET as an international ITER test bed, run by the international community
- Train ITER scientists, engineers and technicians
- Develop ITER technology and scenarios of operation using ITER control tools
  - Upgrades in 2019/2020 with e.g. ECRH, RMPs, refurbishment of divertor, shattered pellet injector, diagnostics,....
- Test ITER schemes for organising and implementing scientific campaigns

International Schedule




[Donné et al., J. Fusion Energy (2015)]

\* Decision to proceed with major enhancements  
 Allow six months to establish project teams for enhancements  
 Details of post-enhancement schedule not yet agreed

## Prepare of ITER operation: ECRH for JET




- 10MW (12 Gyrotrons) at 170 GHz (ITER gyrotrons)
- Antenna: Toroidal and Poloidal steering
- Time to power in plasma: 4 years (7MW), 5-6 years (10MW)
- Prepare ITER operation with similar control strategy: NTM, sawteeth, W control, q-profile etc



Launcher design


[Giruzzi et al., Nucl. Fusion 51 (2011) 063033]



Transmission Lines in Torus Hall

Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 10

## EU Tokamaks with a metallic wall



- **ASDEX Upgrade**
  - Conversion to all W PFCs complete gradually over 7 years
  - Massive outer W-divertor and new divertor manipulator (2014)
- **JET**
  - ITER-like Wall (Be wall and W divertor) change in one shutdown
  - Integrated test with T, D-T scenarios in **2019**
- **Tore Supra → WEST (2016)**
  - from limiter to divertor configuration, from carbon to W environment,
  - Long pulse operation with actively cooled ITER W-monoblocks components


Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 11

## EU contribution: Metallic Walls


- ✓ Provide input to the decision on ITER divertor, wall shaping and DEMO main chamber
- ✓ Demonstrate low fuel retention, migration, dust production and fuel recovery
- ✓ Develop tools and diagnostics (IR) for improved plasma control and heat load mitigation (disruption)
- Demonstrate scenario plasma compatibility with metallic walls
- Test actively cooled ITER mono-block in linear devices and in a plasma environment

Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 12


## Impact on ITER W divertor



- ITER Plasma-Facing Material selection (till 2013)
  - Be/W/C in H/He and Be/W in DD/DT
- AUG and JET-ILW experiments
  - New ITER material selection: Be/ W divertor in all operational phases
- Key input from AUG, JET for divertor PFC change: dedicated melting of a leading edge W lamella



B. Bazylev  
IAEA2014






J.W. Coenen  
NF2015

- Operation with damaged lamella possible
- MEMOS benchmark for ITER predictions

Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 13

## WEST: test of ITER W-divertor components

Upper div : actively cooled W/Cu  
Lower div : mix inertial W/C / few ITER like PFU

➢ WEST : ITER relevant steady state heat loads (10 MW/m<sup>2</sup>) and incidence angle (2-3°)

Phase 1		Act. Cool.	Shaping	Material	Limit
Upper div.		Yes	Yes	W coating / Cu	Flux
Lower div.	Start up	No	Yes	W coating / C	Energy
	ITER like PFU	Yes	No	Bulk W / monoblock	Flux

- **2016-2017:**
  - High power test (10 MW/m<sup>2</sup>) of ITER components
  - shaping comparison
  - test of damaged or below specs components
  - long pulse experiments on W coatings (upper div)

Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 14

## Plasma Facing testing Facilities

- Plasma facilities (+ e-beam, ion beam facilities)

**Magnum-PSI**  
(Restart in 2016)

**PSI-2**  
(operational)

**Pilot-PSI**  
(Not available 2016)

**JULE-PSI from 2017**  
(Be and T compatible)

**WEST**  
(Experiments in 2016)

**PISCES-B for Be/He, Be/D and Be/N exposure**  
(inter. collaboration)

[S. Brezinsek et al]

Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 15

## Impact on ITER Be wall

- Be PFC power-handling exp. in limiter: unexpected narrow power-decay length at the limiter centre
- parallel heat flux not described in SOL with a single decay length  $\lambda_q$

▪ Multi-machine scaling (ITPA) :  
no scaling with machine size

**PFC FLUX      IR measurement**

a)  $\lambda_q = 5\text{mm}$

b)  $\lambda_q = 20\text{mm}$

c)

d)

JET

Toroidal direction →



[Arnoux et al Phys. Scr. 2014, Arnoux et al N.Fus 2014]



[M. Kocan Nucl. Fusion 55 (2015) 033019]

ITER has chosen  $\lambda_q = 4\text{ mm}$  for narrow feature and has redesigned the inner wall toroidal shape in 2014

Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 16







## Tritium studies and Fuel Cycle in JET DT

- **The next DT campaign:**
  - 16 increase in T throughput & feed requirements on the Active Gas Handling System (AGHS) vs 1997
  - 'Tritium Rehearsal' in 2015: exercise AGHS plant & procedures with D2
  - T fuelling with NBI and new gas valves injection
- **Demonstrate T accountability & clean-up techniques with ILW**
  - Upgrade Instrumentation for T measurement
  - Accuracy for T-inventory in AGHS below 0.1g T
- **New water detritiation system: T waste on-site processing and close loop**
- **Train for ITER**
- **Data for Nuclear regulator**

[R Smith, S Knipe, 10th Int. Conf. on T, Nice, 2013,  
B. Wakeling et al 2013]
Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 21

## Neutronics for ITER: measurement and code validation

- **Benchmark ITER calibration procedure for fusion power ( $\leq 10\%$  accuracy) and T accountability**
  - Accurate 14MeV calibration of JET neutron detectors: DT neutron generator deploy by remote handling

[P. Batistoni et al 2015 Nucl. Fusion 55 053028]

- **Technological exploitation of JET DT**
  - Nuclear design, activation, Safety
  - ITER materials radiation damage studies
  - Neutronics code validation for ITER and DEMO: Neutron streaming and shutdown dose rate experiments

JEI
Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 22

## Disruption Physics for ITER

### Highest risk in ITER Research Plan

- Dynamics of disruptions different with metallic walls
- Develop avoidance, prevention and mitigation schemes
- Validation and prediction to ITER

Simulation of Massive Gas Injection (JOREK):  
unstable current profile by cold front penetration

Improved disruption predictors  
(target > 95% for ITER)

Adaptive predictors  
APODIS (data training)  
Mode Lock

[J. Vega, A. Murari et al SOFE 2015 + Nuc Fus 2014 ]

Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 23

## EU Preparation of JT-60SA Exploitation

### Prepare ITER non-inductive operation

ECRH antenna studies

Divertor pumping modelling

[C Day et al EPS 2015 ]

- Prepare for a high level EU participation in JT-60SA scientific exploitation, integrated in the EU fusion programme
- Prepare the EU-JA research plan\*
- Prepare access to data and analysis tools
- Prepare to play an active role in operation & campaigns management

[C Sozzi]      [\*M. Yoshida, G. Giruzzi et al <http://www.it60sa.org/>]

Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 24

# Stellarator - Wendelstein 7-X

## Steady-state facility for physics and technology

European ECRH Expertise for ITER and prepare W7-X


ECRH : ~ 8MW CW at 140GHz; X2, O2

Highest available CW ECRH power

Objectives for ITER


- protection and interlocks
- start-up studies
- Launcher technologies, RAMI

### stray-radiation modeling: validation on W7-X




Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 25

- HELical Advanced Stellarator, HELIAS, line
- Scientific exploitation W7-X including theory & modelling (Plasma operation 2016)
- physics & technology in support of ITER, e.g. ECRH, CW Diagnostics



# First Plasma in W7-X




**Wendelstein 7-X**  
from assembly to operation

- 12.05.2014: Start of commissioning
- 16.07.2015: First flux surface measurements
- 09.12.2015: Operation permit granted
- 10.12.2015: First helium plasma

[W7-X Team , Greifswald, Germany ]

## Wendelstein 7-X

Max-Planck-Institut für Plasmaphysik  
Greifswald (Germany)






### HELIAS-type stellarator

- $N_p=5$ ,  $R/a = 5.5m/0.53m$   
→ **30 m³ plasma volume**
- 50+20 **superconducting** coils (2.5T)
- ~8+7MW (ECRH, NBI) + ICRH (later upgrades)

Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 26

## First Plasma in W7-X

AEQ41\_edi\_20151210\_132821.h5  
Time: 57 ms after T1  
T. Szepesi, C. Biedermann, G. Cseh, G. Kocsis, M. Otte, T. Szabolcs

**Dec. 10th, 2015**

**First helium plasma in W7-X was created according plan**

- Full field: B = 2.52 T
- $P_{\text{ECRH}} = 1.3 \text{ MW}$
- $\tau_{\text{pulse}} = 50 \text{ ms}$

**First measurements of plasma parameters conducted**

- $T_e \sim 100 \text{ eV}$
- $n_e \sim \text{few } 10^{19} \text{ m}^{-3}$


**First shot program (sequence of conditioning pulses) w/ steady-state control system conducted on Dec. 11th**

**[W7-X Team , Greifswald, Germany ]**

Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 27

## W7-X: bring the HELIAS line to maturity

Achieve reliable, steady-state, high  $nT_e\tau_E$  operation  
gain predictive capabilities in view of burning 3D plasmas  
and HELIAS Fusion Power Plant



**uncooled C limiter**  
OP1.1  
pulsed

**C uncooled divertor**  
OP1.2  
pulsed operation

**actively-cooled divertor (CFC)**  
OP2  
steady-state

**metal divertor ?**  
OP3 ...


test-divertor assembly      water-cooled divertor assy

| 2014 | 2015 | 2016 | 2017 | 2018 | 2019 | 2020 | ...

**EUROfusion Mission 8 Stellarator**

Stellarator optimisation      Burning Plasma Stellarator

2010      2020      2030      2040      2050



[A. Dinklage et al 25th IAEA FEC, St. Petersburg, Russia (2014)]

Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 28

## Plasma Heat Exhaust

$Q_{DT} = 10$   
 Reference magnetic equilibrium  
 $P_{IN} = 50 \text{ MW}$   
 $P_{FUS} = 500 \text{ MW}$   
 $P_{\alpha} = 100 \text{ MW}$   
 $P_{RAD} = 50 \text{ MW}$

$P_{OUT} \sim 100 \text{ MW}$   
(~90% to divertor)

[D. J Campbell, ITER research plan]  
 Existing Devices: JET, MST + Linear devices  
 + international collaborations  
 Divertor Test Tokamak?

### Risk mitigation for ITER divertor

- Baseline strategy 'detached' divertor with radiative cooling

### Explore innovative concepts for DEMO

- Alternative divertor solutions with higher flux expansion (Super-X, snowflake) on TCV and MAST
- Advanced PFC (e.g. liquid metals)

Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 29

## ITER Power Decay Length $\lambda_q$ ?

$\lambda_q [\text{mm}]$



$B_{pol,MP} [\text{T}]$

- ◆ MAST
- ▽ NSTX
- ★ C-Mod
- AUG
- ▲ DIII-D
- JET


- $\lambda_q$  scales  $1/I_p$
- ITER  $\lambda_{q,ITER} = 0.9 \pm 0.3 \text{ mm}$
- Dissipation to reduce heat flux?
- Heat load mitigation
- Radiation in the SOL
- Increase divertor broadening

[T. Eich et al FEC 2014, ITPA 2014, PRL 2011]

Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 30







## EU Integrated Modelling for ITER operation

- **Generic approach: not specific to transport simulator problem, to a machine...**
- **Modular, flexible, code, language and machine independent**
- **New data and communication 'ontology' for standardizing the data exchange between codes, with a generic data structure incorporating both simulated & experimental data**
  - modules describing the same physics is easily interchanged
  - eases code coupling & rigorous code verification / benchmark
  - enhanced quality / reproducibility
- **Multi-machine capability: local cluster, GRID, HPC**
- **New HPC in EU for exploitation in 2017**

**EU approach adapted by ITER**  
 ⇒ **IMAS ITER Modelling & Analysis Suite**

**[G. Falchetto et al NF 2014]** Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 34

## European Transport Simulator, ETS

European Transport Simulator, ETS, (multiple physics modules)  
validation on JET, AUG, TCV experiments

### JT-60SA, ITER and DEMO machine description and modelling

**ETS status**

**EQUILIBRIUM:**  
Fixed : BDSEQ, EMEQ,  
SPIDER, HELENA, CHEASE  
FBE: CEDRES++, FREEBIE

**TRANSPORT:**  
Interpretative: ETB (analytical)  
Semi-empirical : BgB  
TCI suite: Weiland, GLF23,  
RITM, MMM, EDWM  
TGLF, Quallikiz  
Neoclassical : NCLASS/FORCEBAL,  
NEOS, NEOWES, NEOART  
Turbulence : GEM

**MHD**  
NTM  
SAWTEETH  
ELMs

**IMPURITIES**  
(all ionization states)

**Position Control**

**ETS**  
1.5D Core Transport Solver

**SOLPS** ↔ **ERO**

**Power controls**

**HCD-sources:**  
ECRH/runaway: GRAY, TRAVIS, TORAFOM,  
C3PO, TORSEAM  
Electron Fokker-Planck: RELAX\*, LUKE\*  
ICRH waves: LION\*, CYRANO\*, EVE\*, TORIC\*  
NBI source: BBNBI\*, NEMO  
Ion Fokker Planck: ASCOT\*, SPOT\*, RISK,  
NBISIM, SixReDist, PION  
nuclear sources: Nuclensim, AFSI\*, DRESS\*

**PELLETS**  
pellet frequency control

**NEUTRALS (fluid)**

**Color code ready under testing ongoing 2016**

Evolution of average electron density, shot 76791

Te at t=5143 s

Ne at t=5143 s

G. Falchetto - WPCD PB 28 November 2015  
Falchetto NF 2014, P. Strand, EU-US TTF2014]

Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 35

## NBI benchmark : Power to the bulk

	AUG	JET	ITER
	Power to the bulk (MW)		
NEMO/NBISIM	19.6	3.8	33
NEMO/RISK	18.4	3.6	32
NEMO/SPOT	-	3.6	33
NEMO/ASCOT	-	3.8	33
BBNBI/NBISIM	19.4	3.8	33
BBNBI/RISK	18.3	3.6	32
BBNBI/SPOT	-	3.7	32
BBNBI/ASCOT	-	3.8	33


- Good agreement for total power to the bulk!
- Wide orbits in ASCOT & SPOT
  - causes losses at edge
  - reshapes central profiles
- NBISIM & RISK **no orbits**

[M. Schneider, ITPA Fast Particles, 2015]


Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 36

## Outline: Europe doing all possible to

**Exploit recent advances in physics and technology to minimise the impact of the revised ITER timeline on the demonstration of fusion electricity:**



- **Support ITER construction and Optimise ITER operation**
  - Risk mitigation for ITER by doing supporting research in contemporary devices



- **Ensure minimal delay to DEMO**
  - Conceptual design System Engineering Approach
  - Address universal technical challenges with gaps beyond ITER
    - o safety, T-breeding, power exhaust, remote handling, component lifetime and plant availability



Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 37

## Design Integration Approach: ITER and DEMO differences

**EU-DEMO the nearest-term reactor to demonstrate production of electricity with a closed fuel cycle.**

	ITER	DEMO
<b>Overall Mission</b>	Experimental device	Approaching a commercial plant
<b>Fusion Power</b>	500MW	~ 2000MW (500 MWe)
<b>Major Radius</b>	6.2m	~ 9m
<b>Pulse Length</b>	6 minutes	~ > 2 hrs
<b>Availability</b>	Exp. campaigns - maintenance and upgrades	Maximize electricity generation
<b>Complexity</b>	Large number of sensors. 6 Test blanket modules, range of concepts Multiple H&CD systems.	Minimised set of sensors Single blanket concept Minimised H&CD mix
<b>Heat Transfer</b>	Cooling system optimized for min. stresses and sized for modest heat rejection.	Cooling system designed for electricity generation (e.g. much higher temp.)
<b>Tritium</b>	No Tritium breeding requirement.	T breeding needed for self-sufficiency.
<b>Materials</b>	Conventional 316 stainless steel structure. PFC: Be wall / W divertor	Novel low activation materials as structure. PFC: full W
<b>Neutrons</b>	n-fluence: ~3 dpa in Steel	n-fluence: ~20 dpa FW steel (1 <sup>st</sup> blank)

[G. Federici and PPPT team]      Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 38



## T Breeding Ratio sensitivity analysis

**Blanket design:**

- Breeder/multiplier materials within a box and covered by a FW.
- Box reinforced by stiffening grids

→ n-absorption by steel

**Blanket size (radial thickness):**

- Inb: ~80 cm / Out: ~130 cm

→ **Requirement: TBR ≥ 1.05** (after integration of diag/ H&CD)

→ ~ 85% of the surface covered by breeding blanket.

→ **Integration:** limited space for divertor, auxiliary systems, limiters etc

**Tritium breeding contributions:**

[P. Pereslavl'tsev et al, C Bachman et al ]

- Improvement of TBR due to divertor size reduction.
- Double Null with two 'small' divertors possible regarding TBR.

[G. Federici and PPPT team]      Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 41

## Tritium Breeding Blanket: four options

**ITER TBM important: qualify fabrication technologies/validate tools, predictive capabilities**

Helium Cooled Pebble Bed (HCPB)

Dual Coolant Lithium Lead (DCLL)

Helium Cooled Lithium Lead (HCLL)


Concept	Breeder/Multiplier	Coolant	T-Extraction	Other
HCPB	Ceramic Breeder / Beryllium	Helium	He low pressure purging	(Permeation control)
HCLL	PbLi	Helium	PbLi slow recirculation	(Corrosion-permeation barrier)
WCLL	PbLi	Water	PbLi slow recirculation	(Corrosion-permeation barrier)
DCLL	PbLi	Helium PbLi	PbLi fast recirculation	FCI of Alumina or SiC/SiC <sub>f</sub>

Water Coolant Lithium Lead (WCLL)

Helium Cooled Lithium Lead (HCLL)


Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 42

## R&D on Material and Early Fusion Neutron Source




**Develop the engineering design of IFMIF-DONES facility, DEMO Oriented Neutron Source**

	IFMIF	IFMIF-DONES
<b>Beam current</b>	2 x 125 mA (Li target)	1 x 125 mA (Li target)
<b>Beam energy</b>	40 MeV	40 MeV
<b>Neutron production</b>	$10^{18}$ n/s	$5 \times 10^{17}$ n/s
<b>Typical Damage Rate</b>	40 dpa/fpy @>60cm <sup>3</sup> + 20 dpa/fpy @>400cm <sup>3</sup>	20 dpa/fpy @>60 cm <sup>3</sup> + 10 dpa/fpy @>400 cm <sup>3</sup>




**IFMIF-DONES preliminary conceptual design**



**IFMIF-DONES Plant Configuration**

[A. Ibarra and WPENS Team] Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 43

## R&D on Materials



- **Fill gaps in the database and develop design codes**
- **Development of new materials to mitigate requirements of advanced DEMO component designs**
- **Demonstration of production in processes scalable to industrial standards**
- **Characterization of material properties**
- **Develop models for neutron radiation effects**
  - microstructural evolution and embrittlement, in iron alloys, steels, tungsten, and degradation of functional materials
- **Develop Structural Design Criteria**
- **Open to international collaboration**

Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 44

## Conclusion: EUROfusion programme is in full swing



### ITER Physics Programme:

- **Programmatic approach in a step-ladder vision for ITER**
  - 2015-2016 simultaneous operation of JET, AUG, TCV, W7-X, WEST and linear PFC
- **Integration of knowledge through theory and modelling for JT-60SA, ITER and DEMO**
- **Preparation for JET D-T operation with ITER-like wall**
- **Internationalization of JET to prepare ITER  $Q_{DT}=10$  operation**
- **Prepare EU to JT-60SA operation**

### Power Plant Physics & Technology Programme

- **INTEGRATED Systems Engineering Approach in the pre-conceptual Design**
- **Integration of Physics, Engineering and Materials science**

Xavier Litaudon | Fusion Power Associates, 36<sup>th</sup> meeting | Washington | 16-17 Dec. 2015 | Page 45